

Date tehnice pentru produs: BK080051--

Dulap distrib. încastr. 1r-12UH, ușă din plastic alb mat



SCHRACK-Info

- Flush-mounted domestic consumer unit enclosures in ABS with solid plastic doors
- Lock: push-button, a small cylinder can be installed
- Includes PE and N terminals
- Protection class II
- Halogen free according to RoHS
- Rated voltage 400VAC / In=63A
- Ambient temperature: -25° to +60°C
- Glow wire test: 650°C
- Recess depth: 68-70mm
- Degree of protection: IP40, Impact resistance: IK08
- RAL9010 pure white

Fișe tehnice

Lățime netă (mm)	282,00
Înălțime (mm)	230,00
Adâncime netă (mm)	106,00
Masă netă (kg.)	0,92
COD EAN	9004840493320

Fișe tehnice - Continuare

disipare (W)	-17,00
Temperatura minimă a mediului ambiant (°C)	-25
Temperatura maximă a mediului ambiant (°C)	60
Versiune	îngropat cu ușă
Material ușă	plastic
Rânduri	1
module / rând	12
Grad de protecție	IP40
Culoare	Alb pur

Tabel articole

Descriere	Cod comandă
Dulap distrib. încastr. 1r-12UH, ușă din plastic alb mat	BK080051
Accesorii opționale	
Încuietoare cilindru metalic pentru BK08... IP40	BK080096